



*The Original Proven 100% Solids Polyurethane*

## ZEBRON 386

### PRODUCT INFORMATION

PRODUCT DESCRIPTION	RECOMMENDED USES																																																																																								
<p><b>Zebtron 386</b> is a 100% solids, spray applied, aromatic "hybrid" polyurethane coating and lining system. It exhibits extraordinary toughness and offers exceptional protection where severe corrosion and severe abrasion exist. It can be applied at thicknesses of 30-250 mils or greater in multiple passes during a single application.</p> <ul style="list-style-type: none"> <li>• Fast cure - short down time</li> <li>• No VOCs and extremely low odor</li> <li>• Seamless, flexible and waterproof</li> <li>• Impact, tear, and abrasion resistant</li> <li>• Chemical resistant</li> <li>• Certified to NSF Standard 61 for a 50 gallon minimum tank size (65 mils maximum)</li> <li>• Highly impermeable.</li> </ul>	<p>Designed for use in immersion or atmospheric exposure as a tough, flexible, impact resistant, waterproof coating and lining system. Ideally suited for use in areas including:</p> <ul style="list-style-type: none"> <li>• Water &amp; Wastewater Linings</li> <li>• Manhole and Sewer Linings</li> <li>• Pipelines</li> <li>• Secondary Containment</li> <li>• Slurry Line</li> <li>• Potable Water Tanks</li> <li>• Tunnels</li> <li>• Offshore Platforms</li> <li>• Fuel storage &amp; Containment</li> </ul>																																																																																								
PRODUCT CHARACTERISTICS	CHEMICAL RESISTANCE																																																																																								
<table> <tr> <td>Finish:</td> <td>Semi-gloss</td> </tr> <tr> <td>Color:</td> <td>Cream</td> </tr> <tr> <td>Volume Solids:</td> <td>100%</td> </tr> <tr> <td>Mix Ratio:</td> <td>3: 1</td> </tr> <tr> <td>VOC (calculated):</td> <td>0</td> </tr> </table> <p>Recommended Spreading Rate per coat:</p> <table> <tr> <td>Wet mils:</td> <td>30.0 - 250.0</td> </tr> <tr> <td>Dry mils:</td> <td>30.0 - 250.0</td> </tr> <tr> <td>Coverage:</td> <td>6 - 53 sq ft./gal approximate</td> </tr> </table> <p>Drying Schedule @ 4.0 mils wet @ 50% RH:</p> <table> <tr> <td></td> <td>@40°F</td> <td>@70°F</td> <td>@120°F</td> </tr> <tr> <td>To touch:</td> <td>1 hour</td> <td>15 min.</td> <td>10 min.</td> </tr> <tr> <td>Tack free:</td> <td>3 hours</td> <td>30 min.</td> <td>15 min.</td> </tr> <tr> <td>To cure:</td> <td>7 days</td> <td>7 days</td> <td>7 days</td> </tr> </table> <p>Pot Life: 10 seconds Sweat-in Time: None</p> <p>Shelf Life: 12 months, unopened Store indoors at 40°F to 100°F Drums must be rotated every 90 days</p> <p>Flash Point: 515°F. COC part A 425°F. COC part B Reducer: Not recommended Clean Up: Toluene, Xylene, or ME</p>	Finish:	Semi-gloss	Color:	Cream	Volume Solids:	100%	Mix Ratio:	3: 1	VOC (calculated):	0	Wet mils:	30.0 - 250.0	Dry mils:	30.0 - 250.0	Coverage:	6 - 53 sq ft./gal approximate		@40°F	@70°F	@120°F	To touch:	1 hour	15 min.	10 min.	Tack free:	3 hours	30 min.	15 min.	To cure:	7 days	7 days	7 days	<table> <tr> <td colspan="2"><b>ACIDS</b></td> </tr> <tr> <td>Phosphoric 50%:</td> <td>No Effect</td> </tr> <tr> <td>Sulfuric 20%:</td> <td>No Effect</td> </tr> <tr> <td>Sulfuric 50%:</td> <td>No Effect</td> </tr> <tr> <td>Acetic 20%:</td> <td>No Effect</td> </tr> <tr> <td>Hydrofluoric 37%:</td> <td>Slight Discoloration</td> </tr> <tr> <td>Hydrofluoric 10%:</td> <td>Surface Cloudiness</td> </tr> <tr> <td>Hydrogen Sulfide:</td> <td>Slight Discoloration</td> </tr> <tr> <td>Chromic 15%:</td> <td>No Effect</td> </tr> <tr> <td>Aqua Regia</td> <td>No Effect</td> </tr> <tr> <td colspan="2"><b>BASES</b></td> </tr> <tr> <td>Sodium Hydroxide 5%:</td> <td>No Effect</td> </tr> <tr> <td>Sodium Hydroxide 33%:</td> <td>No Effect</td> </tr> <tr> <td>Ammonium Hydroxide 5%:</td> <td>No Effect</td> </tr> <tr> <td colspan="2"><b>OTHER CHEMICALS</b></td> </tr> <tr> <td>Magnetite Acid, Paper Mill:</td> <td>No Effect</td> </tr> <tr> <td>Black Liquor, Paper Mill:</td> <td>No Effect</td> </tr> <tr> <td>Oxygenated Wastewater:</td> <td>No Effect</td> </tr> <tr> <td>Raw Sewage:</td> <td>No Effect</td> </tr> <tr> <td>Hydrogen Peroxide 30%:</td> <td>Slight Discoloration</td> </tr> <tr> <td>Chlorine Water (filtrate) 0.1%:</td> <td>Slight Discoloration</td> </tr> <tr> <td>Sodium Hypochlorite 5.25%:</td> <td>Slight Discoloration</td> </tr> <tr> <td>Chlorine Dioxide 1.5%:</td> <td>No Effect</td> </tr> <tr> <td>Sulfure Dioxide 5%:</td> <td>Slight Discoloration</td> </tr> <tr> <td>Magnesium Bisulfite 5%:</td> <td>No Effect</td> </tr> <tr> <td>Water @ Ambient Temp 250°F</td> <td>No Effect</td> </tr> <tr> <td>Petroleum Oils and Greases</td> <td>No Effect</td> </tr> <tr> <td>Soap and Detergent</td> <td>No Effect</td> </tr> </table> <p>(complete list available on request)</p>	<b>ACIDS</b>		Phosphoric 50%:	No Effect	Sulfuric 20%:	No Effect	Sulfuric 50%:	No Effect	Acetic 20%:	No Effect	Hydrofluoric 37%:	Slight Discoloration	Hydrofluoric 10%:	Surface Cloudiness	Hydrogen Sulfide:	Slight Discoloration	Chromic 15%:	No Effect	Aqua Regia	No Effect	<b>BASES</b>		Sodium Hydroxide 5%:	No Effect	Sodium Hydroxide 33%:	No Effect	Ammonium Hydroxide 5%:	No Effect	<b>OTHER CHEMICALS</b>		Magnetite Acid, Paper Mill:	No Effect	Black Liquor, Paper Mill:	No Effect	Oxygenated Wastewater:	No Effect	Raw Sewage:	No Effect	Hydrogen Peroxide 30%:	Slight Discoloration	Chlorine Water (filtrate) 0.1%:	Slight Discoloration	Sodium Hypochlorite 5.25%:	Slight Discoloration	Chlorine Dioxide 1.5%:	No Effect	Sulfure Dioxide 5%:	Slight Discoloration	Magnesium Bisulfite 5%:	No Effect	Water @ Ambient Temp 250°F	No Effect	Petroleum Oils and Greases	No Effect	Soap and Detergent	No Effect
Finish:	Semi-gloss																																																																																								
Color:	Cream																																																																																								
Volume Solids:	100%																																																																																								
Mix Ratio:	3: 1																																																																																								
VOC (calculated):	0																																																																																								
Wet mils:	30.0 - 250.0																																																																																								
Dry mils:	30.0 - 250.0																																																																																								
Coverage:	6 - 53 sq ft./gal approximate																																																																																								
	@40°F	@70°F	@120°F																																																																																						
To touch:	1 hour	15 min.	10 min.																																																																																						
Tack free:	3 hours	30 min.	15 min.																																																																																						
To cure:	7 days	7 days	7 days																																																																																						
<b>ACIDS</b>																																																																																									
Phosphoric 50%:	No Effect																																																																																								
Sulfuric 20%:	No Effect																																																																																								
Sulfuric 50%:	No Effect																																																																																								
Acetic 20%:	No Effect																																																																																								
Hydrofluoric 37%:	Slight Discoloration																																																																																								
Hydrofluoric 10%:	Surface Cloudiness																																																																																								
Hydrogen Sulfide:	Slight Discoloration																																																																																								
Chromic 15%:	No Effect																																																																																								
Aqua Regia	No Effect																																																																																								
<b>BASES</b>																																																																																									
Sodium Hydroxide 5%:	No Effect																																																																																								
Sodium Hydroxide 33%:	No Effect																																																																																								
Ammonium Hydroxide 5%:	No Effect																																																																																								
<b>OTHER CHEMICALS</b>																																																																																									
Magnetite Acid, Paper Mill:	No Effect																																																																																								
Black Liquor, Paper Mill:	No Effect																																																																																								
Oxygenated Wastewater:	No Effect																																																																																								
Raw Sewage:	No Effect																																																																																								
Hydrogen Peroxide 30%:	Slight Discoloration																																																																																								
Chlorine Water (filtrate) 0.1%:	Slight Discoloration																																																																																								
Sodium Hypochlorite 5.25%:	Slight Discoloration																																																																																								
Chlorine Dioxide 1.5%:	No Effect																																																																																								
Sulfure Dioxide 5%:	Slight Discoloration																																																																																								
Magnesium Bisulfite 5%:	No Effect																																																																																								
Water @ Ambient Temp 250°F	No Effect																																																																																								
Petroleum Oils and Greases	No Effect																																																																																								
Soap and Detergent	No Effect																																																																																								